

**Para
PRODUTOS
INDUSTRIAIS**

High-Performance
Flatbed UV Inkjet Printer

Mimaki®

UJF-7151 plus



Criando Mais Valor



RasterLink6

SOFTWARE RIP DE ALTO DESEMPENHO E FÁCIL MANUSEIO


Não significaria nada oferecer diversas funções em software, se o mesmo fosse difícil de operar. O software Raster Link foi desenvolvido para ser operado facilmente, com uma ampla variedade de novos recursos. O software RIP pode ser utilizado por qualquer pessoa, englobando um pacote perfeito com todos os recursos necessários para reproduzir acabamentos cheio de cores vivas em alta definição com controles de fácil navegação.

Specifications

Printhead		On-demand piezo head
Print resolution		600×600dpi, 600×900dpi, 1,200×1,200dpi
Ink	Type	UV curable ink: LH-100 / LUS-120 / LUS-350
		Primer: PR-200
	Package size	250ml bottle(LH-100, LUS-120, PR-200) 1L bottle (LH-100, LUS-120, LUS-350, PR-200)
		Ink circulation function
Maximum printable area		510 × 710 mm (20 × 28 in)
Media	Size(WxDxH)	730 x 530 x 153 mm (28.7 x 20.9 x 6 in)
	Weight	10 kg (22 lb or less)
Media (object) holding method		Vacuum table
Lifting/Lowering range of table		153 mm (6 in)
Interface		USB2.0 / Ethernet
Certifications		"VCCI class A, FCC class A, ETL UL 60950-1CE Marking (EMC, Low voltage, Machinery directive, and RoHS), CB, REACH"
Power supply		Single-phase AC 100 - 240V, 50 / 60 Hz
Power consumption		1,300 VA or less
Operational environment	Temperature	15 ~ 30°C
	Humidity	35 ~ 65 %Rh
	Recommended temperature range for stable operation	20 ~ 25°C
	Allowable range of temperature change	±10°C/h or less
	Dust level	Equivalent to a general office floor level
Dimensions (W×D H)		2,193 x 1,572 x 1,273 mm (86.3 x 61.9 x 50.1 in)
Weight		317 kg (699 lb) Base stand weight is included
RIP software		RasterLink6 (Standard feature)

Options

Mimaki Target Color Emulator	SCE-001	Color emulation software and colorimeter
Mimaki Profile Master II i1ProSet	SPM-005	Color management software and colorimeter



UV-LED lamp

■ UJF-7151 plus

Printheads

LH-100/LUS-120/LUS-350

4C+W CI 1L bottle

UV-LED lamp

■ Conventional model

Printheads

LH-100/LUS-120

4C+W Pr(*6) 1L bottle

*6: Pr implies a primer (PR-200).

Supplies

Item	Item No.	Quantity	Note
LH-100	Cyan LH100-C-BA	1L bottle	"GREENGUARD Gold" Certification Ink
	Magenta LH100-M-BA		
	Yellow LH100-Y-BA		
	Black LH100-K-BA		
	White LH100-W-BA		
LH-100	Clear LH100-CL-BA	250ml bottle	"GREENGUARD Gold" Certification Ink
	Cyan LH100-C-B2		
	Magenta LH100-M-B2		
	Yellow LH100-Y-B2		
	Black LH100-K-B2		
LUS-120	White LH100-W-B2	1L bottle	"GREENGUARD Gold" Certification Ink
	Clear LH100-CL-B2		
	Cyan LUS12-C-BA		
	Magenta LUS12-M-BA		
	Yellow LUS12-Y-BA		
LUS-120	Black LUS12-K-BA	250ml bottle	"GREENGUARD Gold" Certification Ink
	White LUS12-W-BA		
	Clear LUS12-CL-BA		
	Cyan LUS12-C-B2		
	Magenta LUS12-M-B2		
LUS-350	Yellow LUS12-Y-B2	1L bottle	"GREENGUARD Gold" Certification Ink
	Black LUS12-K-B2		
	White LUS12-W-B2		
	Clear LUS12-CL-B2		
	Cyan LUS35-C-BA		
IJ Primer PR-200	Magenta LUS35-M-BA	1L bottle	
	Yellow LUS35-Y-BA		
	Black LUS35-K-BA		
	White LUS35-W-BA		
	Clear LUS35-CL-BA		
Flushing liquid 07	PR200-Z-BA	1L bottle	
	PR200-Z-B2	250ml bottle	
Bottle tightening jig kit	FL007-Z-BA	1L bottle	
Bottle tightening jig kit	SPA-0232	1	
Wiper nozzle	SPA-0274	1	
Waste ink tank	SPA-0277	1	
UV cleaning swab	SPC-0386	10	For head maintenance
UV safety goggles	SPC-0387	1	
Anti freezing liquid	SPC-0394	1,000mlx2	For LED-UV unit
Nozzle swab	SPC-0421	100	Nozzle maintenance liquid
KIM towel	SPC-0499	50	For flushing maintenance
UV primer GM-1	SPC-0541	500ml	Primer for metal and glass
Washing Liquid 100	SPC-0568	100ml	Maintenance liquid
Cleaning kit	SPC-0569	1	UV cleaning swab (10), KIM towel (10), Gloves, washing liquid (100ml x 2), Dropper, Clean stick (10)
Maintenance cloth	SPC-0574	150	For head maintenance
Anti freeze mixed water 35WT%1L	SPC-0783	1,000ml 1	For LED-UV unit
Mist absorption filter	SPC-0816	10	
LED-UV unit filter	SPC-0817	4	

[Print speed]

Print mode	Resolution	Number of passes	Print speed (ml/h)	Print time per print table
Draft	600x600	6	4.21	5 m 10 s
		8	3.14	6 m 55 s
		10	2.56	8 m 30 s
High speed	600x900	12	2.12	10 m 15 s
		16	1.57	13 m 50 s
		12	1.53	14 m 10 s
Standard	1200x1200	16	1.16	18 m 40 s
		16	1.16	18 m 40 s

Print speed: Measured speeds are common for single layer printing (color or spot color single layer) and double-layer printing (color + spot color). Refresh level: 0

ANOTAÇÕES:

Distribuidor autorizado:

Rua Antonio Treis, 549
Bairro Vorstadt - Cep: 89015-400
Blumenau - Santa Catarina
Fone: 47 - 3340-0900
e-mail: contato@galileu.ind.br
Web: www.galileu.ind.br